

REM-2S



NEW TIRE

(E2/L2/G2) EARTHMOVER/LOADER/GRADER

The REM-2S is an all-weather/snow radial OTR tire designed with a wide, non-directional tread pattern for increased traction and year round performance, especially in snow and ice conditions. The tread siping allows for increased traction in severe conditions, while the wide blocks are designed for a flatter footprint and longer tire life. This design makes it an excellent choice in earthmover, loader and grader applications.



PRODUCT CODE	TIRE SIZE	PATTERN	LOAD SYMBOL	SPEED MAX (KM/H)	SPEED MAX (MPH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	TIRE WEIGHT	TIRE TYPE
1107174241	14.00R24 (385/95R24)	REM-2S	★★	50 10	30 5	54	16	30	10.00	12320lb/101psi 20900lb/115psi	135kg/297lb	TL
1107177251	17.5R25	REM-2S	★★	50 10	30 5	53	18	36	14.00/1.5	11990lb/76psi 18700lb/94psi	157kg/345lb	TL
1107170251	20.5R25	REM-2S	★★	50 10	30 5	58	21	39	17.00/2.0	16060lb/76psi 25300lb/94psi	231kg/508lb	TL
1107173251	23.5R25	REM-2S	★★	50 10	30 5	64	24	43	19.5/2.5	20350lb/65psi 31900lb/83psi	321kg/706lb	TL