

REM-28S



(L3/G3/MCS) LOADER/GRADER/ MOBILE CRANE SERVICE TIRE

The REM-28S is designed with a universal tread pattern for increased traction and performance in winter conditions. Its multiple application use includes loader, grader and on-highway, high speed mobile crane wheel positions.

★★★ Star product DOT certified for on-highway use



PRODUCT CODE	TIRE SIZE	PATTERN	LOAD SYMBOL	SPEED MAX (KM/H)	SPEED MAX (MPH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	TIRE WEIGHT	TIRE TYPE
1107308951	14.00R24 (385/95R24)	REM-28S	★★	50	30	54	16	31	10.00	12320lb/101psi	133kg/293lb	TL
1117208952	14.00R25 (385/95R25)	REM-28S	★★★	70	43	54	16	31	10.00/1.5	13948lb/144psi	135kg/298lb	TL
1107300251	17.5R25	REM-28S	★★	50	30	53	18	34	14.00/1.5	11990lb/76psi	152kg/335lb	TL
1107300251	17.5R25	REM-28S	★★	10	5	53	18	34	14.00/1.5	18700lb/94psi	152kg/335lb	TL
1107300751	20.5R25	REM-28S	★★	50	30	58	21	39	17.00/2.0	16060lb/76psi	231kg/509lb	TL
1107300751	20.5R25	REM-28S	★★	10	5	58	21	39	17.00/2.0	25300lb/94psi	231kg/509lb	TL
1107303251	23.5R25	REM-28S	★★	50	30	64	24	45	19.50/2.5	20350lb/65psi	321kg/708lb	TL
1107303251	23.5R25	REM-28S	★★	10	5	64	24	45	19.50/2.5	31900lb/83psi	321kg/708lb	TL