

RLB1/RLB11*

PREMIUM OPEN SHOULDER DRIVE-POSITION TIRE

- Open shoulder design with locking center rib provides a blend of long wear and traction in any environment.
- Tie bar on the outside shoulder helps to maintain stability of the footprint and combat irregular wear.
- Siping in the tread blocks allows the tire to cut through water and debris.
- Robust design provides protection from hazards and job site debris.



PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAM. (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/ PRESSURE	DUAL MAX LOAD/ PRESSURE	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT (LB)	TYPE
1133411255	11R22.5	14	G	144/142	M	41.7	10.9	26	8.25	6175lb/105psi	5840lb/105psi	19.8	493	124	TL
1133411256	11R22.5	16	H	148/145	M	41.7	10.9	26	8.25	6940lb/123psi	6390lb/123psi	19.8	493	128	TL
1133419255	295/75R22.5	14	G	144/141	L	40.9	11.7	26	9.00	6175lb/110psi	5675lb/110psi	19.4	498	129	TL
1133411455	11R24.5	14	G	146/143	L	43.7	10.9	26	8.25	6610lb/105psi	6005lb/105psi	21.0	471	137	TL
1133411456	11R24.5	16	H	149/146	L	43.7	10.9	26	8.25	7160lb/120psi	6610lb/120psi	21.0	471	140	TL
1133418455	285/75R24.5	14	G	144/141	L	41.9	11.0	26	8.25	6175lb/110psi	5675lb/110psi	19.8	485	134	TL
1133412796	225/70R19.5	14	G	128/126	N	32.5	8.8	19	6.75	3970lb/110psi	3750lb/110psi	15.1	644	70	TL
1133414796	245/70R19.5	16	H	136/134	J	33.5	9.6	19	7.50	4940lb/120psi	4675lb/120psi	15.2	617	84	TL
1133419206	9.00R20	16	H	144/142	L	40.6	10.1	26	7.00	6175lb/130psi	5840lb/130psi	19.1	505	119	TT
1133411026	10.00R20	16	H	146/143	L	41.5	10.7	22	7.50	6610lb/120psi	6005lb/120psi	19.4	497	134	TT
1133410225	10R22.5	14	G	141/139	K	40.2	10.0	22	7.50	5675lb/115psi	5355lb/115psi	18.3	512	112	TL
1133415726	255/70R22.5	16	H	140/137	K	36.7	9.9	22	7.50	5510lb/120psi	5070lb/120psi	17.4	560	91	TL
1133419258	295/80R22.5	18	J	152/149	M	41.5	11.7	26	9.00	7830lb/130psi	7160lb/130psi	19.8	493	130	TL
1133971206*	11.00R20	16	H	150/147	L	43.1	11.2	29	8.00	7390lb/120psi	6780lb/120psi	20.2	476	149	TT
1133971208*	11.00R20	18	J	152/149	J	43.0	11.3	23	8.00	7830lb/130psi	7160lb/130psi	20.2	476	149	TT